

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions and listings of claims in the application:

1. (Currently amended) A shackle lock comprising:

a housing;

a locking member formed in the housing;

a shackle ~~further~~ comprising a first end and a second end;

a first connecting member formed at the first end;

a second connecting member formed at the second end, wherein a diameter of the first connecting member is smaller than a diameter of the second connecting member;

a first shackle hole formed in the housing corresponding to the first connecting member; and

a second shackle hole formed in the housing corresponding to the second connecting member, wherein a diameter of the second shackle hole is greater than a diameter of the first shackle hole;

~~wherein the first connecting member passes through the second shackle hole when removing the shackle from the housing~~ the diameter of the second shackle hole is greater than the diameter of the first connecting member and smaller than the diameter of the second connecting member, the first connecting member is allowed to pass through the second shackle hole, and the second connecting member is not allowed to pass through the second shackle hole, and the first connecting member is selectively in a locked position of the shackle lock by operation of the locking member.

2-3. (Canceled)

4. (Withdrawn) The lock of claim 1 further comprising a protruding member extending from the housing.

5. (Withdrawn) The lock of claim 4, the protruding member being rotatable with respect to the housing.

6. (Withdrawn) The lock of claim 1 further comprising a protruding member and a second protruding member extending from the housing, wherein the first and the second shackle holes are respectively formed in the first and the second protruding members.

7. (Withdrawn) The lock of claim 6 further comprising a third protruding member extending from the housing, wherein a third shackle hole is formed in the third protruding member.

8-9. (Canceled)

10. (Currently amended) The lock of claim [[9]] 1, the shackle further comprising an elongated flexible cable.

11. (Currently amended) A shackle lock comprising:

- a housing;
- a locking member formed in the housing;
- a shackle ~~further~~ comprising a first end and a second end;
- a first shackle hole formed in the housing corresponding to the first end; and
- ~~a second shackle hole allowing the first end to pass in a first direction, and blocking the second end to pass in a second direction substantially opposite to the first direction.~~ formed in the housing corresponding to the second end;

wherein a diameter of the second shackle hole is greater than a diameter of the first shackle hole, the second shackle hole allows the first end to pass in a first direction, and blocks the second end to pass in the same first direction, the second shackle hole has a diameter greater than a size of the first end and smaller than a size of the second end, the first end is allowed to pass through the second shackle hole and the second end is not allowed to pass through the second shackle hole, and the first end is selectively in a locked position of the shackle lock by operation of the locking member.

12. (Canceled)

13. (Withdrawn) The lock of claim 11 further comprising a protruding member extending from the housing.

14. (Withdrawn) The lock of claim 13 wherein the first and second shackle holes are formed in the protruding member.

15. (Withdrawn) The lock of claim 13, the protruding member is rotatable with respect to the housing.

16. (Withdrawn) A shackle lock comprising;  
a housing;  
at least one protruding member extending from the housing;  
a shackle further comprising a first end and a second end;  
a first connecting member formed at the first end having a first diameter;  
a second connecting member formed at the second end having a second diameter;  
a first shackle hole corresponding to the first connecting member; and  
at least one second shackle hole corresponding to the second connecting member, each of the at least one second shackle hole having a diameter greater than the first diameter and smaller than the second diameter.

17. (Withdrawn) The lock of claim 16 further comprising a locking member formed in the housing.

18. (Withdrawn) The lock of claim 17, the locking member further comprising a number combination.

19. (Withdrawn) The lock of claim 16 wherein the first shackle hole and the second shackle hole are formed in the at least one protruding member.

20. (Withdrawn) The lock of claim 16, the at least one protruding member being rotatable with respect to the housing.